

BOGOTÁ / EL DORADO
SKBO / STAR RWY 32L/32R

PATH TERM	WAYPOINT NAME	FB FO	ORIENTATION M° (T°)	DISTANCE BETWEEN POINTS (NM)	ALTITUDE + / AT / - / B	SPEED LIMIT (KT) JET + / AT / -	SPEED LIMIT (KT) TURBO + / AT / - / B	TRANSITION IDENTIFIER	RUNWAY DIRECTION
DOPLO 5W									
IF	DOPLO	FB	X	X	FL220 +	X		RW32B	32L;32R
TF	BO822	FB	225° (216.6°)	32	X	X		RW32B	32L;32R
TF	BO824	FB	260° (251.2°)	15	/FL220-FL240/ B	270 -		RW32B	32L;32R
TF	PAPET	FB	259° (251.1°)	20	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR01	FB	283° (274.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR02	FB	257° (249.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR03	FB	231° (223.5°)	9.3	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	TOBKI	FB	205° (197.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	BO885	FB	103° (095.0°)	12.0	X	250 AT	/250-200/B	RW32B	32L;32R
TF	AMVES	FB	103° (095.0°)	8.0	/15000-17000/ B	230 AT	/230-200/B	RW32B	32L;32R
EGEPI 4S									
IF	EGEPI	FB	X	X	16000 +	X		RW32B	32L;32R
TF	MADLA	FB	288° (280.3°)	21	16000 +	250 -		RW32B	32L;32R
ENVAM 5W									
IF	ENVAM	FB	X	X	FL220 +	X		RW32B	32L;32R
TF	BO822	FB	260° (251.2°)	16	X	X		RW32B	32L;32R
TF	BO824	FB	260° (251.2°)	15	/FL220-FL240/ B	270 -		RW32B	32L;32R
TF	PAPET	FB	259° (251.1°)	20	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR01	FB	283° (274.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR02	FB	257° (249.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR03	FB	231° (223.5°)	9.3	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	TOBKI	FB	205° (197.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	BO885	FB	103° (095.0°)	12.0	X	250 AT	/250-200/B	RW32B	32L;32R
TF	AMVES	FB	103° (095.0°)	8.0	/15000-17000/ B	230 AT	/230-200/B	RW32B	32L;32R
ILSEV 5W									
IF	ILSEV	FB	X	X	18000 +	X		RW32B	32L;32R
TF	BO804	FB	199° (190.8°)	36	FL220 -	270 -		RW32B	32L;32R
TF	PAPET	FB	237° (228.6°)	17	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR01	FB	283° (274.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR02	FB	257° (249.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	SUR03	FB	231° (223.5°)	9.3	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	TOBKI	FB	205° (197.5°)	8.7	18000 AT	250 AT	/250-200/B	RW32B	32L;32R
TF	BO885	FB	103° (095.0°)	12.0	X	250 AT	/250-200/B	RW32B	32L;32R
TF	AMVES	FB	103° (095.0°)	8.0	/15000-17000/ B	230 AT	/230-200/B	RW32B	32L;32R
SIRUG 3S									
IF	SIRUG	FB	X	X	15000 +	X		RW32B	32L;32R
TF	OPLEK	FB	250° (241.8°)	31	15000 +	250 -		RW32B	32L;32R

NOTA: * PARA COORDENADAS DE WPT, VER CUADRO COORDENADAS PROCEDIMIENTOS PBN SKBO